





Movie





Virtual Reality Games/ Competition


























 Holes on wall are created by removing components




Holes are used as climbing holders and lighting fixtures




 Pipe and cable sub-channels are integrated in the components design & printing process





Energy & Resources Collection/Distribution







Life Cycle/ Loop (Melissa)


















Personal/ Focused





Design Objective

Furniture integration **vs** landscape adjustment/ extension

Resolution/ Specificity of Surfaces

Stable surfaces i.e. for food/laptop

Spatial Zoning


Privacy levels

Specific predetermined function <u>vs</u> flexibility for further development

Space <-> Body

Size, level difference, degree of openness

Dine Isometric Plan Section



Plan

Life cycle Diagram


radio frequency to Earth

Solar Radiation in orbit Energy

> Photovoltaic PV cells (on surface) for Beam Capture Electricity

Energy Transmission with rovers

Smart Grid



Ice/ Water Collection

Distribution -> Storage

Main areas of habitats (Living, Working) Planters (Food Gallery/Greenhouse)

Grey water treatment

Smart grid and swarm rovers see: water storage system by ESA)

Climate Body Integrated Climate adaptation

Localized suit/ sensors

Habitat Zoning Climate Control

Localized suit/ sensors

Human products

CO2 -> collected

Urine -> Drinkable Water Wall planters Food Ground planters Feces -> Compose Oxygen

Water

Physical integration in design process

Furniture

Planters

Re-use


Melt & Print from materials of previous furniture (Re)Up-cycle

Life support services

Water

Pipes, Wires

Electricity







Figure 9 - Proposed Multi-Layer configuration throughout wall thickness

External/active system

(Scalable solution)
Heat exchange system comprising multiple mirrors, processed lunar soil, a heat engine and heat pipes (ESA)

Integrated/passive system (Building level)

- Placed in Lava Tube
- Covered with Thick Regolith
- Habitat Zoning Climate Control
- Proposed multi layer building skin construction (NASA)



Integrated system (Furniture level)


- Integrated layer of thermal control in several furniture such as beds and lounge chairs

(on earth example: Harness the Heat by MIT)


Embedding thermal control system onto concrete surfaces

Body integrated system


Localized suit layers & sensors





Upper level ◆ Lower level














Eat




Plan





Isometric






Different ground and seating height accommodate close eye levels and different body postures (important for meal gatherings)











Graphics will be adjusted and reproduced asap Photos will be cited asap






Nested Catanery Structure: Gaudi's Chain Model for Colonia Guell Chapel



Graphics will be adjusted and reproduced asap Photos will be cited asap



•1: Primary Direction •2: Secondary Direction



Graphics will be adjusted and reproduced asap Photos will be cited asap




examined. Although not designed for a particular use, these structures provided the opportunity for experiencing the spatial qualities particular to nested catenaries. With its property to minimize the amount of material needed while maximizing the use of its material strength for structural stability and due to relative ease of formwork, this method proved to be economical and suitable for low-tech contexts.

In the design of complex nested catenaries systems, the potential of understanding the effect of geometry in the control of tension in the structure is critical. The effect of the transverse curvature combined with nesting strategy is a direct improvement of the stability and stiffness of the whole construction, making it capable to resist both non-uniform vertical and horizontal loads. The increase of hierarchical levels in the construction introduces high stiffness and provides robustness to the system against local failure. Nesting + Branching by multiplication Curvature + significantly improves shell behavior resulting from the three-dimensional distribution of the shells. The


production of formwork with CNC-milling. As brick-laying is a manual process that can take considerable time and is associated with high-labor costs, it is difficult for brick construction to compete with other construction methods in developed countries. Therefore, it is important to develop procedures that can improve the process of brick-laying.

Structural Assembly (concept diagram)


1. Stacking Method (-)45 to 90 degree





2. Stacking Method 0 to (-)45 degree




3. Long Span (>10m)











Stilt-Root | Structures that grow and expand over time


































2m























2m

